



Introducing the **FL** FLOOD LIGHT/BOX

FL-1



Only
offered
on this
model



-40°F to 104°F (-40°C to 40°C) operating temperature

PowerSet: 19,500/13,000/10,400 lm @ 150/100/80W

3,150 lm @ 30W, 5,250 lm @ 50W,

13,000 lm @ 100W, 19,500 lm @ 150W

Aluminum construction with durable powder coating

Impact-resistant glass lens

Standard G ½ base for Knuckle Accessory

BOX1

150 W



BOX2

300 W



-40°F to 122°F (-40°C to 50°C) operating temperature

PowerSet: 150/100/80/50W; 21,000/15,300/12,500/8,200

lm (120V); 21,000/15,450/12,600/8,250 lm (277V)

300/240/200/150W; 41,300/35,500/29,500/22,900 lm

(120V); 41,600/35,400/29,600/23,000 lm (277V)

Die-cast aluminum heat sink for low weight and
thermal performance

UV resistant polycarbonate optical lens

Durable powder coating for corrosion resistance

Stainless steel hardware

Low profile and versatile
lightweight design

Standard with yoke mount for
easy out-of-the-box installation;
ready for most applications

Easily mounts to waterproof
J-Box wall, pole, or tenon

Includes standard photocell for
dusk-to-dawn functionality

PowerSet feature allows for
multiple "set and forget" lumen
stops in each fixture

Rated lifetime:

L70: >50,000 hours

5000K CCT

FieldCCeT: 50/40/3000K

CRI: >70

Input voltage: 120-277V

0-10V dimming

Power Factor: >0.9

THD: <20%



RoHS
Compliant



CONTACT US TODAY!