LIGHT POLE REQUEST

Agent/Distributor Nar	ne			
Company				
Phone		Email		
Address of Pole Instal	lation			
City	State			ZIP Code
Quantity of Poles (If ordering poles in multiple heights, shapes, etc. please complete a form for each)	Fixtures Mount Option Pre-drilled holes by manufacturer for EiKO's Fixtures only			Are vibration dampeners required? (Internal vibration dampeners are required for projects including, but not limited to: airports, parking ramps, bridges, piers, decks, transportation terminals, etc.)
Poles Part Numer	□AAL1 Adjustable Direct Mount, AAL1-MA			□ Yes □ No
Pre-ship Anchor bolts ☐ Yes ☐ No	☐ AAL1 Fixed Direct Mount, AAL1-FM			Total Fixture/Bracket EPA & Weight (per Pole)
Pole Material ☐ Steel ☐ Aluminum ☐ Other:	□ VERT Adjustable Direct Mount, VRT-D-BZ 180°			Non-Fixture Attachment Mounting (Banners, Flags, Cameras, etc. to be mounted on pole)
Pole Height (ft) ☐ 18' ☐ 20' ☐ 22' ☐ 25' ☐ Other:	270° 0° Handhold □Type D1	□Type D2	□Type D3	Total Non-Fixture EPA & Weight (Banners, Flags, Cameras, etc. to be mounted on pole)
Pole Shape □ Square □ Round □ Other:	1@0°	1@90°; 1@270°	1@0°; 1@120°; 1@240°	Wind Zone of Installation (ZIP Code) Anchorage □ New Footing Install
Finish Color ☐ Bronze ☐ Other:	□Type D4 1@0°; 1@90° 1@180°; 1@270°	□Type D5 1@0°; 1@270°	□Type D6 1@0°; 1@180° 1@270°	(EiKO will supply the bolt kit & template) Address to ship bolt kit
Special Machining Extra Hand Hole cover Festoon Other:	Cap only Slipfitter M Type T1 2.38" Ol	☐ Type Oper ount I D x 4" Long Ten	☐ Existing Bolt Matching (Existing Anchor Bolt Measurement Form to be completed by contractor)	
	conne	cted solu	tions. serv	vice. simplicity. eiko.com